



RO 10

10-position digital magnetic stirrer without heating, designed for synchronous stirring. The magnetic coil technology provides noiseless and consistent stirring on all positions. Speed remains constant, even when load changes. The closed and compact design allows easy cleaning and protects the equipment against the penetration of liquids. Additionally, a removable transparent anti-slip mat is included.

- Adjustable reverse operation
- Wear free magnetic coils
- Error code display
- Easy operation with touch keypad
- Suitable for continuous operation
- Adjustable speed in increments of 10 rpm

Аксессуары: IKAFLON® 20 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round

Технические данные	
Места для перемешивания	10
Макс. объем для одного места (H2O) [l]	0.4
Расстояние между местами [mm]	90
Погрешность одного места для нагрева [%]	0
Макс. Объем (H2O) [l]	4
Индикатор скорости	Диодная линия
Диапазон вращающего момента [rpm]	0 - 1200
Макс. длина магнитного мешалки [mm]	30
Контроль диапазона скоростей	10 RPM Steps
Нагревательная пластина материал	Нерж. сталь 1.4301
Нагревательная пластина размер [mm]	190 x 470
Размеры [mm]	190 x 60 x 570
Вес [kg]	5
Допустимая температура окружающей среды [°C]	5 - 40
Допустимая относительная влажность [%]	80
Класс защиты согласно DIN EN 60529	IP 40
Напряжение [V]	100 - 240
Частота [Hz]	50/60
Потребляемая мощность [W]	25
Постоянное напряжение [V=]	24
Энергопотребление [mA]	1000
Идент.No.	0003691000

PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, BC 1000 Beaker cap, H11 сетевой шнур, вилка для Китая, H11 сетевой шнур, вилка для USA, H11 сетевой шнур, евровилка, RSE Извлекатель магнитных мешалников, H11 сетевой шнур, вилка для Великобритании