



### C-MAG MS 4 IKAMAG®

Аксессуары: RS 1 Набор магнитных мешалочников для перемешивания, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated

Технические данные	
Места для перемешивания	1
Макс. Объем (H <sub>2</sub> O) [l]	5
Потребляемая мощность привода [W]	15
Производимая мощность привода [W]	1.5
Индикатор скорости	Шкала
Диапазон вращающего момента [гpm]	100 - 1500
Контроль диапазона скоростей	Шкала 0-6
Нагревательная пластина материал	Керамика
Нагревательная пластина размер [mm]	100 x 100
Размеры [mm]	150 x 105 x 260
Вес [kg]	3
Допустимая температура окружающей среды [°C]	5 - 40
Допустимая относительная влажность [%]	80
Класс защиты согласно DIN EN 60529	IP 21
Напряжение [V]	230 / 120 / 100
Частота [Hz]	50/60
Потребляемая мощность [W]	30
Идент.No.	0003582200

Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, RSE Извлекатель магнитных мешалников, H 16 V Штатив, LABLIFT m, BC 1000 Beaker cap